

# Profile Selection Guide



## High-Quality Compression Sealing

Schlegel PolyFab® is a premier line of foam, PP, TPE, and dual-extrusion gaskets. From custom windows and doors to office cubicles and other building and product projects, PolyFab® sealing products provide consistent quality that is unsurpassed in the industry.

Schlegel EMI brings 40 years of expertise in sealing gaskets to the construction industry with the PolyFab® line.

All parts shipped from Schlegel EMI are RoHS and REACH compliant.

## PolyFab® Properties



**Highly engineered embossed polyethylene liner**

- Resists paints and varnishes
- Long lasting
- Maintains an attractive appearance



**UV stabilized**

- Stable in sunlight (UV stable)
- Tested up to 5,000 Kj/m<sup>2</sup> with no visible degradation



**Resilient urethane open-celled foam**


- Shape and resiliency are retained over time
- Offers excellent all temperature sealing performance
- No corner leaks
- Seal conforms to uneven surfaces



**Dual durometer insert**

- Allows for easy insertion and maximum retention
- It is removable without damaging jamb or seal

## Part Number Guide (Foam Gaskets)









(\*) UL10C, Standard for positive pressure fire tests of door assemblies.

(\*\*) SillGuard Black (Fine Satin Embossed):





















Hydrostatic Resistance: 115psi. Flame Resistance, after flame: (sec) ≤ 2.0

## Liner

















Black (BL)	White (WH)	Brown (BR)	Beige (BE)	Grey (GR)	SillGuard Black (BK)
					

Tensile Strength (psi)	3450
Compression Set	<15% (compressed at 50% during 22 Hrs. @ 70°C)
Heat Conductivity W/mK	0.06 at 0°C
Operating Temperature	-60 to 70°C

## Profiles (Foam Gaskets)

<b>P4U*</b>	<b>P66</b>	<b>P4X</b>	<b>P4E*</b>	<b>P4F*</b>
				
2.54mm x 6.6mm .100" x .260"	6.35mm x 9.53mm .250" x .375"	6.4mm x 8.3mm .252" x .327"	6.6mm x 6.6mm .260" x .260"	8.5mm x 8.5mm .335" x .335"
<b>P63</b>	<b>P68</b>	<b>P90*</b>	<b>P10</b>	<b>P4P*</b>
				
9.53mm x 9.53mm .375" x .375"	9.53mm x 12.7mm .375" x .500"	3.56mm x 6.35mm .140" x .250"	6.35mm x 9.53mm .250" x .375"	3.8mm x 4.8mm .150" x .189"
<b>P41*</b>	<b>P4T*</b>	<b>P4S*</b>	<b>PQ2*</b>	<b>P4R*</b>
				
5.08mm x 4.83mm .200" x .190"	5.1mm x 6.9mm .201" x .272"	5.7mm x 4.8mm .224" x .189"	6.35mm x 4.83mm .250" x .190"	6.4mm x 6.9mm .252" x .272"
<b>P5K</b>	<b>P5N</b>	<b>P53</b>	<b>P4Q</b>	<b>P3W</b>
				
7.0mm x 6.9mm .276" x .272"	7.6mm x 4.8mm .300" x .189"	7.62mm x 6.86mm .300" x .270"	9.53mm x 4.83mm .375" x .190"	9.53mm x 6.86mm .375" x .270"






## Profiles (Foam Gaskets)

PH3*	P4V	P98*	P85	P4C*
				
8.0mm x 8.0mm .315" x .315"	8.79mm x 11.3mm .346" x .445"	9.78mm x 10.67mm .385" x .420"	11.8mm x 10.7mm .465" x .421"	12.42mm x 15.06mm .489" x .593"
P4M	P4W	P32	P3X*	P5A*
				
16.5mm x 14.7mm .650" x .579"	16.51mm x 14.73mm .650" x .580"	17.15mm x 14.73mm .675" x .580"	18.79mm x 15.62mm .740" x .615"	19.5mm x 16.6mm .768" x .654"
P4N	P3Y*	P60	P4Y	P5J
				
20.9mm x 14.7mm .823" x .579"	23.52mm x 15.77mm .926" x .621"	3.3mm x 13.2mm .130" x .520"	9.68mm x 24.0mm .381" x .945"	5.5mm x 33.4mm .217" x 1.315"
P5B				
				
5.54mm x 42.9mm .218" x 1.689"				

## Part Number Guide (Thermoplastic Elastomer "TPE" Gaskets)

PTXX — BL — T — 00000  
 |           |           |           |  
 Profile    Color      Tape      Length  
 Shape

## Profiles (Thermoplastic Elastomer "TPE" Gaskets)

PT01	PT02	PT03	PT04	PT05
				
9.42mm x 6.35mm .371" x .250"	14.29mm x 9.53mm .562" x .375"	12.7mm x 14.3mm .500" x .563"	5.8mm x 13.5mm .228" x .531"	11.1mm x 12.5mm .437" x .492"

More profile options available. Contact us at [schlegelpolyfab@schlegelemi.com](mailto:schlegelpolyfab@schlegelemi.com)

## Applications



**Workplace Infrastructure**



**Door Installation**



**Window Weatherstripping**



**Construction Screen Installation**

And many more!



Contact us at [schlegelpolyfab@schlegelemi.com](mailto:schlegelpolyfab@schlegelemi.com)

## NORTH AMERICA

### Schlegel Electronic Materials, Inc.

1600 Lexington Ave  
Suite 236A Rochester NY 14606  
Tel No: +1 585-643 2000  
Fax No: +1 585-427 7216  
Email: [schlegelemi.na@schlegelemi.com](mailto:schlegelemi.na@schlegelemi.com)

## EUROPE

### Schlegel Electronic Materials, bv

Slijpesteenweg 28  
8432 Middelkerke (Leffinge)  
Belgium  
Tel No: +32 59 560 270  
Fax No: +32 59 560 271  
Email: [schlegelbe@schlegelemi.com](mailto:schlegelbe@schlegelemi.com)

## ASIA

### Schlegel Electronic Materials Asia Limited

Unit 3, 3/F., Block A, New Trade Plaza,  
6 On Ping Street, Shatin, N.T., Hong Kong  
Tel No: +852-2686 9872  
Fax No: +852-2686 9728  
Email: [schlegelemi@emeigroup.com](mailto:schlegelemi@emeigroup.com)

### Schlegel (Dongguan) Electronics Limited

No. 8 Qiaoxin Road, Qiaotou, Dongguan,  
Guangdong, China  
Postal Code: 523525  
Tel No: +86-769-8356 5686  
Fax No: +86-769-8334 5656  
Email: [schlegelemi@emeigroup.com](mailto:schlegelemi@emeigroup.com)

### Schlegel (Shanghai) Electronics Limited

4/F., 79 Parts, 111 Meisheng Road,  
F.T.Z., Pudong, Shanghai, China  
Postal Code: 200131  
Tel No: +86-21-5868 3383  
Fax No: +86-21-5868 3386  
Email: [schlegelemi@emeigroup.com](mailto:schlegelemi@emeigroup.com)

### Taiwan Schlegel Electronics Limited

No. 99, Alley 3, Lane 182, Section 2 Wenhua Road,  
Banqiao District  
Postal Code: 22044  
Tel No: +886-2-8258 5148  
Fax No: +886-2-8258 5149  
Email: [schlegelemi@emeigroup.com](mailto:schlegelemi@emeigroup.com)



[polyfabfeedback@schlegelemi.com](mailto:polyfabfeedback@schlegelemi.com)



[www.linkedin.com/company/schlegelemi](http://www.linkedin.com/company/schlegelemi)

**Schlegel PolyFab**<sup>®</sup>  
*Passion For Quality*

[www.schlegelemi.com](http://www.schlegelemi.com)  
[www.schlegelemi.com/polyfab](http://www.schlegelemi.com/polyfab)